

OFF- GRID INVERTER

Axpert MAX TWIN



- Dual outputs, for smart load management
- Maximum PV input current increases to 27A
- Wide PV input voltage range 90VDC ~ 450VDC
- Replaceable fan design for ease of maintenance
- Built-in Wi-Fi for mobile monitoring (Android/iOS App is available)
- Compatible to Utility Mains or generator input
- Reserved communication port for BMS (RS485, CAN-BUS or RS232)
- Status indication with RGB lights
- Battery independent design
- Selectable high power charging current
- Supports USB On-the-Go function
- Built-in anti-dust kit
- Parallel operation with 6 units



Axpert MAX TWIN Off-Grid Inverter Selection Guide

MODEL	Apert MAX TWIN 8K	Apert MAX TWIN 11K
Rated Power	8000VA/8000W	11000VA/11000W
Parallel Capability	YES, 6 units	
INPUT		
Voltage	230 VAC	
Selectable Voltage Range	170-280 VAC (For Personal Computers) ; 90-280 VAC (For Home Appliances)	
Frequency Range	50 Hz/60 Hz (Auto sensing)	
OUTPUT		
AC Voltage Regulation (Batt. Mode)	230VAC ± 5%	230VAC ± 5%
Surge Power	16000VA	22000VA
Efficiency (Peak)	93%	
Transfer Time	10 ms (For Personal Computers) ; 20 ms (For Home Appliances)	
Waveform	Pure sine wave	
DC Voltage	12 VDC ± 5%, 100W	N/A
BATTERY		
Battery Voltage	48 VDC	48 VDC
Floating Charge Voltage	54 VDC	54 VDC
Overcharge Protection	66 VDC	63 VDC
SOLAR CHARGER & AC CHARGER		
Solar Charger Type	MPPT	
Maximum PV Array Power	8000W (4000W x 2)	11000W (5500W x 2)
MPPT Range @ Operating Voltage	90 ~ 450 VDC	90 ~ 450 VDC
Maximum PV Array Open Circuit Voltage	500 VDC	500 VDC
Maximum PV Input Current	27A x 2 (MAX 40A)	
Maxmum Solar Charge Current	120A	150A
Maximum AC Charge Current	120A	150A
Maximum Charge Current	120A	150A
PHYSICAL		
Dimension, D x W x H (mm)	147.4 x 432.5 x 553.6	
Net Weight (kgs)	18.4	
Communication Interface	USB, RS232, RS485, WiFi, Dry-contact	
OPERATING ENVIRONMENT		
Humidity	5% to 95% Relative Humidity(Non-condensing)	
Operating Temperature	-10°C to 50°C	
Storage Temperature	-15°C to 60°C	
STANDARD		
Compliance Safety	CE	

Product specifications are subject to change without further notice.

